


Fiber Optic Distribution Box

FTT-FDB12-B



Product Description

FTT-FDB12-B Fiber Optic Splitter Distribution Box is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile it provides solid protection and management for the FTTx network building.

Feature

- ◆ PC+ABS, wet-proof, water-proof, dust-proof, anti-aging, protection level up to IP65.
- ◆ Cable, pigtails, patch cords are running through own path without disturbing each other, cassette type SC adaptor installation, easy maintenance.
- ◆ Distribution panel can be flipped up, feeder cable can be placed by expression port, easy for maintenance and installation.
- ◆ Cabinet can be installed by the way of wall-mounted or poled-mounted, suitable for both indoor and outdoor uses.

Application

- ◆ Widely used in FTTH access network.
- ◆ Telecommunication Networks
- ◆ CATV Networks
- ◆ Data communications Networks

◆ Local Area Networks



Specification

Product No.	FTT-FDB12-B
Dimension(LxWxH)	274*175*82 mm
Cable entries	Inlet port: 4 ports Outlet port: 12 ports
Splicing Tray	12/24 fiber per tray
Max. capacity	12 cores
Material	ABS+PC
PLC splitter	1*4,1*8,1*12 Mini Steel Tube/ bare type PLC splitter
No. of Adapter	Max. 12pcs SC SX 12pcs LC DX Adapter
IP rating	IP65
Cable Entry	Support un-cutting

More Photos

