Fiber Optic Distribution Box

H8







Product Description

H8 Fiber Optic Splitter Distribution Box is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile it provides solid protection and management for the FTTx network building.

Feature

- ◆ PP+ GEL SEALING, wet-proof, water-proof, dust-proof, anti-aging, protection level up to IP68.
- ◆ Cable, pigtails, patch cords are running through own path without disturbing each other, cassette type SC adaptor installation, easy maintenance.
- Distribution panel can be flipped up, feeder cable can be placed by expression port, easy for maintenance and installation.
- ◆ Cabinet can be installed by the way of wall-mounted or poled-mounted, suitable for both indoor and outdoor uses.

Application

- ◆ Widely used in FTTH access network.
- ◆ Telecommunication Networks
- ◆ CATV Networks
- ◆ Data communications Networks

◆ Local Area Networks

Specification	
Product No.	H8
Dimension(LxWxH)	252*210*72 mm
Cable entries	Inlet port: 2 ports Outlet port: 8 ports
Splicing Tray	8 fiber per tray
Max. capacity	8 cores
Max Cable Diameter	16mm
Material	PP+ gel sealing
PLC splitter	1*4,1*8 Mini Steel Tube/ bare type PLC splitter
No. of Adapter	Max. 8pcs SC SX
	8pcs LC DX Adapter
IP rating	IP68
Cable Entry	Support un-cutting

More Details





Accessories

1. Inter cable port sealing accessory for seal cable port if don't need use all of them.





2. Drop cable sealing accessory for seal drop cable port if don't need use all of them







3. Inter cable diameter adjuster, for cable diameter 8mm, 10mm, 14mm .



